




### Features:

Series of surface mounted downlight, made of diecast Aluminum body, PMMA cover with Anti-yellowing properties.  
Available in different wattage ranges with very wide beam angle  
High light Transmissivity.  
Homogenous, well-balanced light dispersing, no shadow.



### Technical Specifications:

Input Voltage : 220- 240 V AC, 50 Hz.  
Wattage : 12 - 24W  
High Lumen : 110lm/W  
3 STEP Mac Adam  
CRI> 80  
Lamp Type : SMD  
Operating Temperature: -20°C to 60°C  
Glow Wire Test 850° C  
Warranty : 5 Years  
Life Time : 50,000hrs at ta 25°C (L80/B10)

### Fields of Application:

Corridor  
Toilet  
Bedrooms  
Kitchen

### Installation Method:

Surface & Ceiling mounted.

Wattage(W)	:	12	15	24
Finish	:	White	Black	
Kelvin*	:	3000K	4000K	6500K
Beam Angle	:	120°		
Type	:	A	B	C
Driver	:	ON/OFF	0/1-10V	DALI Phase Dimming

\*Special Color & Finish on request

### Product Parameter:

Product Code	Wattage	Lumens(lm)	Dimension(Ø x H)
96316812	12	1320LM	220 X 38 mm
96321515	15	1650LM	220 X 38 mm
96330024	24	2640LM	220 X 38 mm

\*Luminous flux value is calculated for 4000K & CRI>80

### Standards

EN 60598-1  
EN 60598-2-2  
EN 60598-2-22  
EN 61000-3-2  
EN 61000-3-3  
EN 61547  
EN 55015

### Photometric:

