

Features:

This is outdoor wall mounted bulkhead, made of Polycarbonate body, PMMA frosted cover with Anti-yellowing properties.
Built-in waterproof rubber ring, for outdoor IP65 protection.
Stainless steel screws.
High light Transmissivity.
Homogenous, well-balanced light dispersing, no shadow.

Technical Specifications:

Input Voltage : 220- 240 V AC, 50
Hz. Wattage : 12 - 18W
High Lumen : 100lm/W
4 STEP Mac Adam
CRI> 80
Isolated driver, surge protection 2KV
Lamp Type : SMD
Operating Temperature: -20°C to 60°C
Glow Wire Test 850° C
Warranty : 5 Years
Life Time : 50,000hrs at ta 25°C (L80/B10)

Fields of Application:

Boundary Wall
Balcony
Roof
Shaft

Installation Method:

Surface & Ceiling mounted.

Wattage(W)	:	12	15	18
Finish	:	White	Black	
Kelvin*	:	3000K	4000K	6500K
Beam Angle	:	120°		
Type	:	A	B	C
Driver	:	ON/OFF	0/1-10V	DALI Phase Dimming

*Special Color & Finish on request

Product Parameter:


Product Code	Wattage	Lumens(lm)	Dimension(Ø x H)
96327512	12	1200LM	275 X 86
96327515	15	1500LM	275 X 86
96327518	18	1800LM	275 X 86

*Luminous flux value is calculated for 4000K & CRI>80

Standards

EN 60598-1
EN 60598-2-2
EN 60598-2-22
EN 61000-3-2
EN 61000-3-3
EN 61547
EN 55015

Photometric:



Additional Options:

Photocell (Dusk to Dawn)
PIR/Motion Sensor
Emergency backup kits