

STICK



Features:

STICK is a family of surface mounted linear LED lights for wall washing and general illumination. It comes with different CCT and RGB+W LED sources. It has very wide application like flat contour, terraced landscape, urban lighting, subway, viaduct, internal and external walls of buildings, etc.

Fields of Application : Parking Lots / Shopping Malls / Landscaping / School Safety / Parks & Garden


Technical Specifications:

Wattage : 10-12W
 Input Voltage : 220- 240 V AC, 50/60 Hz.
 High Lumen : 100lm/W
 3 STEP Mac Adam
 Isolated constant current driver
 Lamp Type : SMD
 Operating Temperature: -20°C to 55°C
 Glow Wire Test 650° C
 Warranty : 5 Years
 Life Time : 50,000hrs at ta 35°C L80 / B10

Product Specifications:

Material: High Strength Aluminum
 Coating: Electrostatic powder coated
 Bracket: SS304
 Glass: Tempered Glass
 Power Cable: Power cable included
 Driver: Remote
 Adjustable: Yes

Installation Method : Surface Mounted



Wattage(W)	:	10	12				
Finish	:	White (W)	Black(B)	Grey(G)	Customizable(C)		
Kelvin*	:	2700K	3000K	4000K	5000K	6000K	RGB RGBW
Beam Angle	:	120°					
CRI	:	80+	90+				
Driver	:	ON/OFF	0/1-10V	DALI	DMX		


*Special Color & Finish on request

Product Code (862202012):

Wattage	Lumens(lm)	Dimension(WxHxL) mm
10	1000LM	20x20x1525
12	1200LM	20x20x1525

Customized Length and Wattage on request .

Photometric:



Standards

EN 60598-1
 EN 60598-2-2
 EN 60598-2-22
 EN 60598-3-2

Order Code Ex: 862202012 27K 120D : 8 1 B

CCT	Beam Angle	CRI	Driver	Finish
27K-2700K 30K-3000K 40K-4000K 50K-5000K 60K-6000K RGB-RGB RGBW-RGBW	120D-120°	8->80 9->90	1-ON/OFF 2-0/1-10V 3-DALI 4-DMX 5-Bluetooth	White(W) Black(B) Grey(G) Customizable(C)

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C